#### LIQUID COLOR SYSTEMS



# **ColorSelect<sup>®</sup> Liquid Concrete Products System**


The Solomon ColorSelect<sup>®</sup> System is a fully integrated, automated system designed specifically for use in Manufactured Concrete Products Operations.





#### SYSTEM

- State-of-the-art technology designed for precast, paver, and masonry unit producers
- 400 gallon stationary V-bottom totes with a pigment agitation system
- Quickly and efficiently batch thousands of colors using 4 or 5 primary color ColorFlo<sup>®</sup> Liquid pigments



- Windows-based PC control system & software
- 3.5 gallon weigh vessel mounted on a platform scale, equipped with an automatic wash-out feature
- Remote Service Technicians available 24/7



solomoncolors.com | (800) 624-0261

## **ColorSelect<sup>®</sup> Liquid Concrete Products System**

#### **EFFICIENT OPERATION**

- The Solomon ColorSelect System uses state-of-the-art technology to affordably achieve accuracy and performance.
- Once installed and properly programmed by Solomon Colors technicians, your plant operator will be able to input data into the computer using terms that are familiar in the concrete industry.
- You can store a virtually unlimited number of formulas in the Solomon ColorSelect<sup>®</sup> System for instant recall. Adjustments for color, aggregates, or cement are quick and easy to make.



For a complete overview of the Color System along with Site Requirements, please contact your local Solomon Colors Representative. 062322MOD

#### SPECIFICATIONS

- Manual or automatic fill and dump cycles
- 4 (or 5) APEX hose pumps
- 4 (or 5) conical-bottom stationary supply totes
- 400 gal. capacity each
- Remote PC-based interface with emergency stop
- Air wand recycle system
- 60 lb Batch Capacity

### FOOTPRINT

- Main panel: 8" x 24" x 36"
- 3.5 gal. weigh chamber: 22" x 20" x 43"

#### REQUIREMENTS

- Electrical: Main power 230 V or 460 V 3-phase
- Control circuits 110 V
- Communication Ethernet
- Plumbing: Pump suction 1.5" suction hose Pigment Lines 3/4" nylon tube
- Gravity Discharge— 1" rubber hose
  Optional pump
- Air: 80-100 PSI, 5 CFM, 3/8" FPT
- Water: 40-50 PSI continuous pressure, 3/4" FPT



solomoncolors.com | (800) 624-0261